

Asterisk Appliance

IP-01



System:

Open Source uClinux

Hardware:

CPU: 400MHz Blackfin 532 Chip
 One analog (FX0/FXS) module interface.
 NAND flash 256 M
 SDRAM 64M

Features:

Open Source Asterisk IP PBX
 Voiptel GUI
 High performance OSLEC (Open Source Line Echo Canceller)
 Configurable IVR menu.
 Voice Mail
 Call forward, call waiting, call transfer
 Call conference ,Call queues
 SIP trunking, IAX trunking ,PSTN analog trunk
 Flexible dial plan

Interfaces:

1 X RJ45 port.
 1 X Power port.
 1 X RS232 port.
 1 X RJ11 port. (FXS/FX0 configurable)

Accessories:

Power adaptor
 FX0/FXS module

Applications:

SOHO application
 FAX terminal
 IVR

Size:

100 x 100 x 28 MM

IP PBX series models:

Model No.	RJ45	TEL Ports	RS232 Port	Others	Size(mm)
IP-01	1	1 x fxs/fxs	1 fix RS232 port	--	100 x 100 x 28
IP-01P	1	1 x fxs	1 fix RS232 port	POE	100 x 100 x 28
IP-02	2	2 x fxs/fxo	1 RS232 module	--	100 x 100 x 28
IP-04	1	4 x fxs/fxs	1 RS232 module	MMC	225 x 120 x 30
IP-08	2	8 x fxs/fxs	1 RS232 module	MMC,USB	225 x 120 x 30
IP-BRI	1	4 x BRI	1 fix RS232 port	MMC,EC module(option)	225 x 120 x 30

